

WHAT IS CLAIMED IS:

1. A bumper or guard comprising:
a thickened pad having a flat bottom;
an elongated shaft having a distal end providing a wedge
and an opposite end having a retention head; and
said head embedded in said pad with said shaft outwardly
projecting from said pad.
2. The bumper or guard defined in Claim 1 wherein:
said pad is dome-shaped with a flat circular underside;
said shaft projecting from said flat circular underside
along a longitudinal axis of said pad; and
said pad composed of a semi-rigid material adapted to
permit penetration by jagged edges.
3. The bumper or guard defined in Claim 2 wherein:
said pad includes a plurality of cavities opening
through said flat circular bottom; and
said cavities defining a plurality of reinforcement ribs.
4. The bumper or guard defined in Claim 3 including:
a core provided in said pad joined by said reinforcement
ribs; and
said shaft outwardly projecting from said core.

5. The bumper or guard defined in Claim 4 wherein:
said distal end includes a pair of flat surfaces
converging together to form a wedge tip.

6. A protective bumper or guard comprising:
a dome-shaped pad of semi-rigid material;
said pad having a flat bottom defined by a circular
peripheral edge;
an elongated shaft of rigid material having a wedged tip
at one of its two ends and a retention head at its other end for
securement in said pad;
said head having outwardly projecting flanges embedded
in said semi-rigid material for retaining said shaft along a
central longitudinal axis of said pad; and
said pad adapted to receive penetration of jagged edges
and points.

7. The protective bumper and guard defined in Claim 6
including:
said dome-shaped pad having an apex with a recess therein;
and
an identification disk secured in said recess below and
an exterior surface of said pad.

8. The protective bumper and guard defined in Claim 7 including:

a plurality of cavities in said semi-rigid material opening through said flat bottom to define a plurality of reinforcement ribs.

9. The protective bumper and guard defined in Claim 8 including:

a central core between said cavities for supporting said shaft so as to cantilever outwardly from said pad from said flat bottom.

10. The protective bumper and guard defined in Claim 9 wherein:

said semi-rigid material is of a flexible and soft composition.